

DATASHEET

Return to the Webpage 🕥



Features

- ±5VDC
- 1A

Specifications

Power Supply ±5VDC, 1A. Detectors, Amplifiers

Parameter	Min	Typical	Max	Unit
Output Voltage		±5		VDC
Output Current		1		А
Connector Type	N			
Compatible Products	De			

Applications

- Power Supply
- Detectors, Amplifiers

Note: The specifications provided are for general applications with a cost-effective approach. If you need to narrow or expand the tolerance, coverage, limit, or qualifications, please [click this <u>link</u>]:

Legal notices: All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind Agiltron only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with the use of a product or its application.


Rev 05/21/25		
© Photonwares Corporation	P +1 781-935-1200 E sales@photonwares.com	www.agiltron.com



DATASHEET

Mechanical Dimensions (mm)

Mechanical Dimensions (mm) -- Connector



*Product dimensions may change without notice. This is sometimes required for non-standard specifications.

© Photonwares Corporation

P +1 781-935-1200 E sales@photonwares.com

www.agiltron.com



DATASHEET

Ordering Information

				1	1	1	1
Prefix	Output Voltage	Output Current	Connector Type				
DDC-	±5VDC = 05	1A = 10	M8 3 Pin Connector = 1				

need to check

Application Notes

© Photonwares Corporation

P +1 781-935-1200 E sales@photonwares.com W


www.agiltron.com



DATASHEET

Power Connector

Power Barrel Connector Jack 2.00mm ID (0.079"), 5.50mm OD (0.217") Through Hole, Right Angle



*Product dimensions may change without notice. This is sometimes required for non-standard specifications.

© Photonwares Corporation

P +1 781-935-1200 E sales@photonwares.com W www.agiltron.com